

Solar Street Light						
Model:	EAL-SL25				Mounting height (m)	5-6m
Solar Panel Max Power	18V/50W				Space between lights (m)	18-20m
Solar Panel Life Span	25 years				Fixture body	Aluminium Alloy
Battery Type	Lithium Battery (Life Span 5 years)					
LED Max Power	12V 25W				Warranty Period:	2 years
LED Chip Brand	Bridgelux				Unit Size:	1150 x 330 x 140mm
Lumen (LM)	3000-3250lm				N.W:	17.65kg
LED Life Span	50000 hours					
Lighting Viewing Angle	120°				Carton size:	1190 x 400 x 220mm
Charge time	6-7 hours				Q'ty/ctn:	1set/ctn
Discharge Time	more than 20 hours (saving mode)				GW. For carton	18.6kg
Working Temp (°C)	20-+60					
CCT (k)	6500k-7000k					
Model:	EAL-SL50				Mounting height (m)	7-8m
Solar Panel Max Power	18V/80W				Space between lights (m)	25-30m
Solar Panel Life Span	25 years				Fixture body	Aluminium Alloy
Battery Type	Lithium Battery (Life Span 5 years)					
LED Max Power	12V 50W				Warranty Period:	2 years
LED Chip Brand	Bridgelux				Unit Size:	1080 x 450 x 153mm
Lumen (LM)	6000-6500lm				N.W:	20kg
LED Life Span	50000 hours					
Lighting Viewing Angle	120°				Carton size:	1180 x 510 x 200
Charge time	6-7 hours				Q'ty/ctn:	1set/ctn
Discharge Time	10 hours				GW. For carton	22.5kg
Working Temp (°C)	20-+60					
CCT (k)	6500k-7000k					