

EC03 LED Spot Downlight (Fixed Type)								
Model No.	Power	Input Voltage	Colour Temperature	Luminous Flux	Size	Cutout	Power Factor	Beam Angle
EC03-COB-D10W	10W	AC220-240V	3000k - 6500k	800lm	130dia. x 95mm	120mm	> 0.95	15° to 60°
		50-60Hz						
EC03-COB-D15W-A	15W	AC220-240V	3000k - 6500k	1100lm	130dia. x 95mm	120mm	> 0.95	15° to 60°
		50-60Hz						
EC03-COB-D15W-B	15W	AC220-240V	3000k - 6500k	1100lm	160dia. x 100mm	150mm	> 0.95	15° to 60°
		50-60Hz						
EC03-COB-D20W-A	20W	AC220-240V	3000k - 6500k	1600lm	160dia. x 100mm	150mm	> 0.95	15° to 60°
		50-60Hz						
EC03-COB-D20W-B	20W	AC220-240V	3000k - 6500k	1600lm	190dia. x 110mm	175mm	> 0.95	23° to 60°
		50-60Hz						
EC03-COB-D30W	30W	AC220-240V	3000k - 6500k	2400lm	190dia. x 110mm	175mm	> 0.95	23° to 60°
		50-60Hz						
EC03 LED Spot Downlight (Gimbal Type)								
Model No.	Power	Input Voltage	Colour Temperature	Luminous Flux	Size	Cutout	Power Factor	Beam Angle
EC03-COB-GD10W	10W	AC220-240V	3000k - 6500k	800lm	110dia. x 80mm	90mm	> 0.95	15° to 60°
		50-60Hz						
EC03-COB-GD15W-A	15W	AC220-240V	3000k - 6500k	1100lm	110dia. x 80mm	90mm	> 0.95	15° to 60°
		50-60Hz						
EC03-COB-GD15W-B	15W	AC220-240V	3000k - 6500k	1100lm	140dia. x 90mm	120mm	> 0.95	15° to 60°
		50-60Hz						
EC03-COB-GD20W-A	20W	AC220-240V	3000k - 6500k	1600lm	140dia. x 90mm	120mm	> 0.95	15° to 60°
		50-60Hz						
EC03-COB-GD20W-B	20W	AC220-240V	3000k - 6500k	1600lm	160dia. x 95mm	145mm	> 0.95	23° to 60°
		50-60Hz						
EC03-COB-GD30W	30W	AC220-240V	3000k - 6500k	2400lm	160dia. x 95mm	145mm	> 0.95	23° to 60°
		50-60Hz						